# DUNA
# L1222-3K


IP65 IK08


**DUNA LED 18/34W 3000K 3150/5350lm IP66**

The DUNA is an airtight polycarbonate diffuser specifically designed to provide perfectly uniform LED lighting while delivering optimal luminous performance. It can be equipped with cross wiring.



| | |
|---|---|
| **CODE** | L1222-3K |
| **POWER (W)** | 18W-23W-29W-34W |
| **AUTONOMY (U)** | |
| **TYPE** | |
| **RESCUE (LM)** | |
| **PERMANENT (LM)** | 3150lm-3900lm-4650lm-5350lm |
| **BATTERY** | |




## Features

| | |
|---|---|
| PRODUCT NAME | DUNA |
| PRODUCT FUNCTION | HERMETIC LED LIGHTING |
| SYSTEM POWER (W) : | 18W-23W-29W-34W |

LINERGY
EMERGENCY LIGHTING

# DUNA
# L1222-3K

| | |
|---|---|
| CONSUMPTION POWER (ABSORPTION) | 18W-34W |
| CONTINUOUS MODE LUMINOUS FLOW (LM) : | 3150lm-3900lm-4650lm-5350lm |
| WITH CONNECTION TO A IMPULSE RELAY | YES |
| POWER SUPPLY (V) : | 220-230V |
| LIGHT SOURCE | LED |
| WITH LIGHT SOURCE | YES |
| PROTECTION CLASS | IP65 |
| HOUSING MATERIAL | POLYCARBONATE |
| HOUSING COLOUR | GRIS RAL 7035 |
| MATERIAL OF THE COVER | PMMA PROTECTION UV 20% OPALE |
| IMPACT RESISTANCE | IK08 |
| HEIGHT/DEPTH (MM) : | 84mm |
| LENGTH (MM) : | 1277mm |
| WIDTH (MM) : | 101mm |
| MOUNTING WIDTH | 800mm |
| PRODUCT WEIGHT (G) : | 2900GR |
| INCANDESCENT WIRE 850°C | OUI |
| WIRING TYPE | ADAPTE A UN CÂBLAGE TRANVERSANT |
| CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC | YES |
| VOLTAGE TYPE | AC |
| MAX. OF LUMINAIRES PER B16 CIRCUIT BREAKER (TWO-POLE) | 48 |
| MAX. OF LUMINAIRES PER C16 CIRCUIT BREAKER (SINGLE) | 48 |
| NONIMAL LIFETIME L70/B50 (H) : | 100.000H (L70/B50) |
| RATED AMBIENT TEMPERATURE TO IEC 62722-2-1 | -5°C / +55°C |
| COLOUR TEMPERATURE | 3000K |
| GUARANTEE | 5 YEARS |
| TYPE OF PACKAGING | CARTON BOX |
| NUMBER OF UNITS IN PACKAGING | 1 |
| INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES | YES |
| BEBAT CODE | - |
| RECUPEL CODE | 4.56 |
| BATTERY WEIGHT (G) : | 0 |
| EAN | 9900000003876 |
| INTRASTAT CODE | 85394900 |
| COMPLIANT WITH EUROPEAN STANDARDS | EN 60598-1<br>EN 60598-2-22 |

| | |
|---|---|
| INSTALLATION METHOD | Surface mounting (ceiling)<br>Surface mounting (wall)<br>Surface mounting (wall/ceiling) |
| LIGHT DISTRIBUTION ELEMENT | Reflector |
| MODE | Light ON/OFF<br>Standard |
| PROTECTION CLASS | I |

## Accessories

**LDUNA-TRANS3P** - DUNA TRANSVERSE WIRING 3P



**LDUNA-TRANS5P** - DUNA TRANSVERSE WIRING 5P



**LATE002** - MALE CONNECTOR WIELAND RST20I5S



**LATE003** - CONNECTOR FEMALE WIELAND RST20I5S



**L6100** - 2-PIECE ANTI-VANDALISM MOUNTING

