DUNA
L1222HI-DET


IP66 IK08


DUNA LED 38/52W 4000K 6200/8100lm IP66 + SENSOR

The DUNA is an airtight polycarbonate diffuser specifically designed to provide perfectly uniform LED lighting while delivering optimal luminous performance. It can be equipped with cross wiring.



CODE	L1222HI-DET
POWER (W)	38W-45W-48W-52W
AUTONOMY (U)	
TYPE	
RESCUE (LM)	
PERMANENT (LM)	6200lm-7150lm-7450lm-8100lm
BATTERY	





Features

PRODUCT NAME	DUNA
PRODUCT FUNCTION	HERMETIC LED LIGHTING
SYSTEM POWER (W) :	38W-45W-48W-52W

DUNA
L1222HI-DET

CONSUMPTION POWER (ABSORPTION)	38W-52W
CONTINUOUS MODE LUMINOUS FLOW (LM) :	6200lm-7150lm-7450lm-8100lm
SURVEILLANCE SYSTEM INSTALLATION	SANS
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP66
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	GRIS RAL 7035
MATERIAL OF THE COVER	PMMA PROTECTION UV 20% OPALE
IMPACT RESISTANCE	IK08
HEIGHT/DEPTH (MM) :	84mm
LENGTH (MM) :	1277mm
WIDTH (MM) :	101mm
MOUNTING WIDTH	800mm
PRODUCT WEIGHT (G) :	2900GR
INCANDESCENT WIRE 850°C	OUI
WIRING TYPE	ADAPTE A UN CÂBLAGE TRANVERSANT
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
VOLTAGE TYPE	AC
MAX. OF LUMINAIRES PER B16 CIRCUIT BREAKER (TWO-POLE)	25
MAX. OF LUMINAIRES PER C16 CIRCUIT BREAKER (SINGLE)	38
NONIMAL LIFETIME L70/B50 (H) :	100.000H (L70/B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	-5°C / +55°C
COLOUR TEMPERATURE	4000K
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	-
RECUPEL CODE	4.56
BATTERY WEIGHT (G) :	0
EAN	9900000000301
INTRASTAT CODE	85394900
COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-1 EN 60598-2-22

FUNCTION	Lighting with detection Twilight
INSTALLATION METHOD	Surface mounting (ceiling) Surface mounting (wall) Surface mounting (wall/ceiling)
LIGHT DISTRIBUTION ELEMENT	Reflector
MODE	Light ON/OFF
PROTECTION CLASS	I

Accessories

LDUNA-TRANS3P - DUNA TRANSVERSE WIRING 3P



LDUNA-TRANS5P - DUNA TRANSVERSE WIRING 5P



LATE002 - MALE CONNECTOR WIELAND RST20I5S



LATE003 - CONNECTOR FEMALE WIELAND RST20I5S



L6100 - 2-PIECE ANTI-VANDALISM MOUNTING

