DUNA
L1211-SE-3H-AUT


IP66 IK08


DUNA LED 9W/17W 4000K 1600/2700lm - 620lm IP66 3h + EMERGENCY AUT

The DUNA is an airtight polycarbonate diffuser specifically designed to provide perfectly uniform LED lighting while delivering optimal luminous performance. It can be equipped with cross wiring.



CODE	L1211-SE-3H-AUT
POWER (W)	9W-12W-14W-17W
AUTONOMY (U)	3h
TYPE	Not permanent-Permanent
RESCUE (LM)	620lm
PERMANENT (LM)	1600lm-1950lm-2300lm-2700lm
BATTERY	LI-FEPO4





Features

PRODUCT NAME	DUNA
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED HERMÉTIQUES
SYSTEM POWER (W) :	9W-12W-14W-17W

LINERGY
EMERGENCY LIGHTING

DUNA
L1211-SE-3H-AUT

CONSUMPTION POWER (ABSORPTION)	9W-17W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	620lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	1600lm-1950lm-2300lm-2700lm
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
BATTERY	Li-FeP04 3,2V 7,5Ah
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP66
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	GRIS RAL 7035
MATERIAL OF THE COVER	PMMA PROTECTION UV 20% OPALE
IMPACT RESISTANCE	IK08
HEIGHT/DEPTH (MM) :	84mm
LENGTH (MM) :	660mm
WIDTH (MM) :	101mm
MOUNTING WIDTH	390mm
PRODUCT WEIGHT (G) :	1200GR
INCANDESCENT WIRE 850°C	OUI
WIRING TYPE	ADAPTE A UN CÂBLAGE TRANVERSANT
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
MAX. OF LUMINAIRES PER B16 CIRCUIT BREAKER (TWO-POLE)	70
MAX. OF LUMINAIRES PER C16 CIRCUIT BREAKER (SINGLE)	116
NONIMAL LIFETIME L70/B50 (H) :	100.000H (L70/B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	-5°C / +55°C
COLOUR TEMPERATURE	4000K
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020001
RECUPEL CODE	4.56
BATTERY WEIGHT (G) :	218 gr.
EAN	9900000003845
INTRASTAT CODE	85365000

COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 EN 62034
FUNCTION	Ambient and evacuation lighting Ambient lighting (anti-panic)
INSTALLATION METHOD	Surface mounting (ceiling) Surface mounting (wall) Surface mounting (wall/ceiling)
LIGHT DISTRIBUTION ELEMENT	Reflector
MODE	Autotest Light ON/OFF Security
NOMINAL OPERATING TIME	3h
PROTECTION CLASS	I
TYPE OF SWITCHING	Not permanent Permanent

Accessories

LDUNA-TRANS3P - DUNA TRANSVERSE WIRING 3P



LDUNA-TRANS5P - DUNA TRANSVERSE WIRING 5P



LATE002 - MALE CONNECTOR WIELAND RST20I5S



LATE003 - CONNECTOR FEMALE WIELAND RST20I5S



L6100 - 2-PIECE ANTI-VANDALISM MOUNTING

