FLAG
LFG1701


IP40 4 pcs

FLAG 4,5W 30m 1SPY CENTER


The Flag model is made of a sleek anodized aluminum body and 56 white LEDs, providing high brightness. It harmoniously combines its two functions: Emergency & Signaling.



CODE	LFG1701
POWER (W)	4,5W
AUTONOMY (U)	
TYPE	Not permanent- Permanent
RESCUE (LM)	120lm
PERMANENT (LM)	
BATTERY	



A=317mm B=168mm C=60mm
D=16mm E=43mm F=159mm



Features

PRODUCT NAME	FLAG
PRODUCT FUNCTION	EMERGENCY AND SIGNAL LIGHTING
SYSTEM POWER (W) :	4,5W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	120lm
SIGHT DISTANCE (M) :	30M
SURVEILLANCE SYSTEM INSTALLATION	SANS
POWER SUPPLY (V) :	220-230V

BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP40
HOUSING MATERIAL	FONTE D'ALUMINIUM
HOUSING COLOUR	GREY RAL 9006
HEIGHT/DEPTH (MM) :	60mm
LENGTH (MM) :	317mm
MOUNTING WIDTH	168mm
PRODUCT WEIGHT (G) :	1500GR
NUMBER OF PRODUCTS PER BOX	4
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
INCLUDED PICTOGRAMS	OUI
VOLTAGE TYPE	AC
RATED VOLTAGE	230V
NONIMAL LIFETIME L70/B50 (H) :	100.000H
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
COLOUR TEMPERATURE	6000K
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	45 gr.
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 RoHS2 2011/65/UE
FUNCTION	Ambient and evacuation lighting
INSTALLATION METHOD	Surface mounting (wall)
LIGHT DISTRIBUTION ELEMENT	Diffuser
MODE	Security Spy center
PICTOGRAM VISIBILITY	Only on one side
PROTECTION CLASS	I
TYPE OF PICTOGRAM	Placed sheet/plate
TYPE OF SWITCHING	Not permanent Permanent

Accessories

L99020-30-FG - FLAG KIT OF PICTOS



LA323 - FLAG WALL FIXATION



L99150 - COMMANDER

