LINEA-LED
LLN2402

IP40 IK08 16 pcs

LINEA LED 8,4W 585lm 3h M/NM WIRELESS

The LINEA LED wall unit offers excellent light performance, with up to 800 lumens, thanks to its 40 LED light sources. Its slim and elegant aluminum body gives it a sleek and refined style.



CODE	LLN2402
POWER (W)	8,4W
AUTONOMY (U)	3h
TYPE	
RESCUE (LM)	585lm
PERMANENT (LM)	785lm
BATTERY	LI-FEPO4



A=300mm B=55mm C=35mm



Features

PRODUCT NAME	LINEA-LED
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES
SYSTEM POWER (W) :	8,4W

LINEA-LED
LLN2402

LIGHT OUTPUT IN EMERGENCY MODE (LM) :	585lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	785lm
SURVEILLANCE SYSTEM INSTALLATION	WIRELESS
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP40
HOUSING MATERIAL	ALUMINIUM
HOUSING COLOUR	ALUMINIUM RAL 9007
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK08
HEIGHT/DEPTH (MM) :	55mm
LENGTH (MM) :	300mm
WIDTH (MM) :	35mm
NUMBER OF PRODUCTS PER BOX	16
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020590
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	84
EAN	8021046122657
INTRASTAT CODE	85365000

COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-1 EN 60598-2-22 EN 61347-1 EN 61347-2-13 EN 61347-2-7 EN 62031 EN 62384 RoHS2 2011/65/UE
FUNCTION	Ambient lighting (anti-panic)
INSTALLATION METHOD	Surface mounting (wall)
MODE	Wireless/Spy system wireless
NOMINAL OPERATING TIME	3h
PROTECTION CLASS	II

Accessories

L99150 - COMMANDER



LA305 - INHIBITION KIT FOR PERMANENT VERSION

