
IK06


QUBE 26m BC CENTRAL BATTERY IP32



CODE	L24326
POWER (W)	
AUTONOMY (U)	3h
TYPE	Permanent
RESCUE (LM)	
PERMANENT (LM)	
BATTERY	



A=175mm B=179mm C=175mm



Features

PRODUCT NAME	QUBE
PRODUCT FUNCTION	LUMINAIRES DE SIGNALISATION LED NON HERMETIQUES
SURVEILLANCE SYSTEM INSTALLATION	SANS
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP32

HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	NOIR RAL 7021
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK06
HEIGHT/DEPTH (MM) :	175mm
LENGTH (MM) :	175mm
WIDTH (MM) :	179mm
MOUNTING WIDTH	175mm
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
INCLUDED PICTOGRAMS	OUI
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	-
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	0
EAN	8021046118223
INTRASTAT CODE	85365000
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 RoHS2 2011/65/UE
FUNCTION	Ambient and evacuation lighting Evacuation lighting
INSTALLATION METHOD	Chain Hanging Surface mounting (ceiling) Surface mounting (wall) Surface mounting (wall/ceiling)
LIGHT DISTRIBUTION ELEMENT	Reflector
MODE	Centralized battery Security
NOMINAL OPERATING TIME	3h
PROTECTION CLASS	II

TYPE OF SWITCHING	Permanent

Accessories

LKITQU26ISO - QUBE SET OF PICTOS 26m

