STORM
L25027-N

IP66 IK10

STORM LIGHT 18W 5000K 1500lm IP66 BLACK



CODE	L25027-N
POWER (W)	18W
AUTONOMY (U)	
TYPE	
RESCUE (LM)	
PERMANENT (LM)	1500lm
BATTERY	

Features

PRODUCT NAME	STORM
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED HERMÉTIQUES
SYSTEM POWER (W) :	18W
CONTINUOUS MODE LUMINOUS FLOW (LM) :	1500lm
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP66
HOUSING MATERIAL	FONTE D'ALUMINIUM
HOUSING COLOUR	NOIR RAL 7021
MATERIAL OF THE COVER	VERRE TRANSPARENT
IMPACT RESISTANCE	IK10
HEIGHT/DEPTH (MM) :	120mm

STORM
L25027-N

LENGTH (MM) :	202mm
WIDTH (MM) :	202mm
INCANDESCENT WIRE 850°C	OUI
NONIMAL LIFETIME L70/B50 (H) :	100.000H
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	-20°C / +40 °C
COLOUR TEMPERATURE	5000K
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
BEBAT CODE	-
RECUPEL CODE	5.56
EAN	9900000008086
EAN PACK	9900000008406
INTRASTAT CODE	85365000
COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-1 EN 60598-2-22
FUNCTION	Twilight
INSTALLATION METHOD	Surface mounting (wall)
LIGHT DISTRIBUTION ELEMENT	Reflector
MODE	Light ON/OFF
PROTECTION CLASS	I