
SWING
L9703-DALI-OUT

IP30 IK06 2 pcs


SWING OUT 3W 30m 1h P DALI



CODE	L9703-DALI-OUT
POWER (W)	3W
AUTONOMY (U)	1h
TYPE	Permanent
RESCUE (LM)	
PERMANENT (LM)	
BATTERY	NI-CD



A=450mm B=50mm C=1mm
D=300mm E=15mm
F=188mm G=225mm



Features

PRODUCT NAME	SWING
PRODUCT FUNCTION	LUMINAIRES DE SIGNALISATION LED NON HERMETIQUES
SYSTEM POWER (W) :	3W
SIGHT DISTANCE (M) :	30M
SURVEILLANCE SYSTEM INSTALLATION	DALI
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4

SWING
L9703-DALI-OUT

BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP30
HOUSING MATERIAL	ALUMINIUM
HOUSING COLOUR	GREY RAL 9007
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK06
HEIGHT/DEPTH (MM) :	225mm
LENGTH (MM) :	305mm
WIDTH (MM) :	35mm
MOUNTING WIDTH	305mm
PRODUCT WEIGHT (G) :	3300GR
NUMBER OF PRODUCTS PER BOX	2
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	NI-CD
INCLUDED PICTOGRAMS	OUI
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B207035090
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	41
EAN	8021046120820
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 RoHS2 2011/65/UE
FUNCTION	Evacuation lighting

INSTALLATION METHOD	Chain Hanging Surface mounted recessed Surface mounting (ceiling) Surface mounting (wall) Surface mounting (wall/ceiling)
MODE	Dali Security
NOMINAL OPERATING TIME	1h
TYPE OF SWITCHING	Permanent

Accessories

L91041-30 - PICTO ASTRA DOWN 30M



L99150 - COMMANDER

