TUBE-LED
L6528HI-90-AC-DC


IP67 IK10


TUBE 56/70W 4000K 7600/9200lm IP67 AC-DC

The TUBE LED is a tubular, industrial-style, multifunctional model that offers very high luminous output, exceptional impact resistance (IK10), and excellent waterproofing thanks to its 3.5 mm thick UV-resistant polycarbonate tube.



CODE	L6528HI-90-AC-DC
POWER (W)	56W-61W-66W-70W
AUTONOMY (U)	
TYPE	
RESCUE (LM)	
PERMANENT (LM)	7600lm-8100lm-8650lm-9200lm
BATTERY	





Features

PRODUCT NAME	TUBE-LED
PRODUCT FUNCTION	HERMETIC LED LIGHTING

LINERGY EMERGENCY LIGHTING

TUBE-LED
L6528HI-90-AC-DC

SYSTEM POWER (W) :	56W-61W-66W-70W
CONSUMPTION POWER (ABSORPTION)	56W-70W
CONTINUOUS MODE LUMINOUS FLOW (LM) :	7600lm-8100lm-8650lm-9200lm
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP67
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	GREY RAL 9007
MATERIAL OF THE COVER	POLYCARBONATE OPAL
IMPACT RESISTANCE	IK10
HEIGHT/DEPTH (MM) :	90mm
LENGTH (MM) :	1570mm
WIDTH (MM) :	90mm
MOUNTING WIDTH	1570mm
PRODUCT WEIGHT (G) :	3200GR
INCANDESCENT WIRE 850°C	OUI
WIRING TYPE	ADAPTE A UN CÂBLAGE TRANVERSANT
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
VOLTAGE TYPE	AC-DC
MAX. OF LUMINAIRES PER B16 CIRCUIT BREAKER (TWO-POLE)	50
MAX. OF LUMINAIRES PER C16 CIRCUIT BREAKER (SINGLE)	85
NONIMAL LIFETIME L70/B50 (H) :	100.000H (L70/B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	-5°C / +55°C
COLOUR TEMPERATURE	4000K
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	-
RECUPEL CODE	4.56
BATTERY WEIGHT (G) :	0
EAN	9900000009250
INTRASTAT CODE	85394900
COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-1 EN 60598-2-22

TUBE-LED
L6528HI-90-AC-DC

INSTALLATION METHOD	Chain Hanging Surface mounting (ceiling) Surface mounting (wall) Surface mounting (wall/ceiling)
LIGHT DISTRIBUTION ELEMENT	Reflector
MODE	Light ON/OFF Standard
PROTECTION CLASS	I

Accessories

LTUBE-TRANS3P - TUBE TRANSVERSE WIRING 3P



LTUBE-TRANS5P - TUBE TRANSVERSE WIRING 5P



LATE002 - MALE CONNECTOR WIELAND RST20I5S



LATE003 - CONNECTOR FEMALE WIELAND RST20I5S



L6100 - 2-PIECE ANTI-VANDALISM MOUNTING

