# VIALED-EVO-MINIBOX
## L8126-N-DALI-BOX


IP42 IK08 12 pcs

**VIALED EVO MINIBOX 5,7W 410lm 3h M/NM BLACK DALI**


The Vialed Evo MINIBOX is the minimalist surface-mounted version of the Vialed Evo. It comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation.




| | |
|---|---|
| **CODE** | L8126-N-DALI-BOX |
| **POWER (W)** | 5,7W |
| **AUTONOMY (U)** | 3h |
| **TYPE** | Permanent |
| **RESCUE (LM)** | 410lm |
| **PERMANENT (LM)** | 410lm |
| **BATTERY** | |




A=130mm B=130mm
C=125mm D=40mm




## Features

| | |
|---|---|
| PRODUCT NAME | VIALED-EVO-MINIBOX |
| PRODUCT FUNCTION | LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES |
| SYSTEM POWER (W) : | 5,7W |

# VIALED-EVO-MINIBOX
## L8126-N-DALI-BOX

| | |
|---|---|
| LIGHT OUTPUT IN EMERGENCY MODE (LM) : | 410lm |
| CONTINUOUS MODE LUMINOUS FLOW (LM) : | 410lm |
| SURVEILLANCE SYSTEM INSTALLATION | DALI |
| WITH CONNECTION TO A IMPULSE RELAY | YES |
| WITH REMOTE CONTROL (COMMANDER) | YES |
| POWER SUPPLY (V) : | 220-230V |
| BATTERY | LiFePO4 |
| LIGHT SOURCE | LED |
| WITH LIGHT SOURCE | YES |
| PROTECTION CLASS | IP42 |
| HOUSING MATERIAL | POLYCARBONATE |
| HOUSING COLOUR | NOIR RAL 9005 |
| MATERIAL OF THE COVER | LENTILLE TRANSPARENTE |
| IMPACT RESISTANCE | IK08 |
| HEIGHT/DEPTH (MM) : | 40mm |
| LENGTH (MM) : | 130mm |
| WIDTH (MM) : | 130mm |
| MOUNTING WIDTH | 125mm |
| PRODUCT WEIGHT (G) : | 1200GR |
| NUMBER OF PRODUCTS PER BOX | 12 |
| INCANDESCENT WIRE 850°C | OUI |
| VOLTAGE TYPE | AC |
| NONIMAL LIFETIME L70/B50 (H) : | 50.000H (L70B50) |
| RATED AMBIENT TEMPERATURE TO IEC 62722-2-1 | 0°C / +40 °C |
| GUARANTEE | 5 YEARS |
| TYPE OF PACKAGING | CARTON BOX |
| NUMBER OF UNITS IN PACKAGING | 1 |
| INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES | YES |
| BEBAT CODE | B209035180 |
| RECUPEL CODE | 5.56 |
| BATTERY WEIGHT (G) : | 81 gr. |
| EAN | 8021046126204 |
| EAN PACK | 8021046359978 |

# VIALED-EVO-MINIBOX
# L8126-N-DALI-BOX


| | |
|---|---|
| COMPLIANT WITH EUROPEAN STANDARDS | EN 1838<br>EN 60598-1<br>EN 60598-2-22<br>EN 61347-1<br>EN 61347-2-13<br>EN 61347-2-7<br>EN 62031<br>EN 62384<br>EN 62386-101<br>EN 62386-102<br>EN 62386-202<br>EN 62386-207<br>RoHS2 2011/65/UE |
| FUNCTION | Ambient and evacuation lighting |
| INSTALLATION METHOD | Surface mounting (ceiling) |
| LIGHT DISTRIBUTION ELEMENT | Focal lens<br>Refraction lens |
| MODE | Dali<br>Security |
| NOMINAL OPERATING TIME | 3h |
| PROTECTION CLASS | II |
| TYPE OF SWITCHING | Permanent |

## Accessories

**LA341** - VIALED EVO MINIBOX SUSPENDED PLEXI KIT



**LA305** - INHIBITION KIT FOR PERMANENT VERSION



**L99150** - COMMANDER

