VIALED-HIGH
L8104HI-N


IP20 IP42 IK07 8 pcs


VIALED HIGH 0,4W 3h 360lm AUT NM BLACK


The Vialed High is designed for high ceilings. Discreet and efficient, it comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation. The metal ring is available



CODE	L8104HI-N
POWER (W)	0,4W
AUTONOMY (U)	3h
TYPE	Not permanent
RESCUE (LM)	360lm
PERMANENT (LM)	
BATTERY	LI-FEPO4







Features

PRODUCT NAME	VIALED-HIGH
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES

LINERGY
EMERGENCY LIGHTING

VIALED-HIGH
L8104HI-N

SYSTEM POWER (W) :	0,4W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	360lm
WITH CONNECTION TO A IMPULSE RELAY	YES
WITH REMOTE CONTROL (COMMANDER)	YES
POWER SUPPLY (V) :	220-230V
BATTERY	Li-FeP04 3,2V 3Ah
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP20/IP42
HOUSING MATERIAL	FONTE D'ALUMINIUM
HOUSING COLOUR	NOIR RAL 9005
MATERIAL OF THE COVER	LENTILLE TRANSPARENTE
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	3,2mm
EXTERNAL DIAMETER (MM) :	85mm
FLUSH-MOUNTED DIAMETER (MM) :	65mm
MOUNTING WIDTH	85mm
PRODUCT WEIGHT (G) :	1600GR
NUMBER OF PRODUCTS PER BOX	8
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
ENEC	YES
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020590
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	81 gr.
EAN	8021046119435
EAN PACK	8021046336917

COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 EN 61347-1 EN 61347-2-13 EN 61347-2-7 EN 62031 EN 62034 EN 62384 RoHS2 2011/65/UE
FUNCTION	Ambient and evacuation lighting Ambient lighting (anti-panic)
INSTALLATION METHOD	Built-in Surface mounted recessed
LIGHT DISTRIBUTION ELEMENT	Focal lens Refraction lens
MODE	Autotest Security
NOMINAL OPERATING TIME	3h
PROTECTION CLASS	II
TYPE OF SWITCHING	Not permanent

Accessories


L99193-B - VIALED APPARENT BOX 185X185 WHITE




L99193-N - VIALED APPARENT BOX 185X185 BLACK



L99193-G - VIALED APPARENT BOX 185X185 GREY



L99157 - INHIBITION KIT FOR PERMANENT VERSION




L99194-B - VIALED RECESSED 165X165 WHITE

L99194-N - VIALED RECESSED PLATE 165X165 BLACK



L99194-G - VIALED RECESSED PLATE 165X165 GREY



L99150 - COMMANDER

