VIALED-NET
LVE1801-G


IP20 IK07 8 pcs

VIALED NET EVO 4,5W 360lm GREY


The Vialed Net remote power system allows you to connect up to four Vialed luminaires in a fully flexible configuration—star, cascade, or mixed. This system is ideal for spaces that are difficult to access or very confined.




CODE	LVE1801-G
POWER (W)	4,5W
AUTONOMY (U)	1h
TYPE	
RESCUE (LM)	360lm
PERMANENT (LM)	360lm
BATTERY	



A=182mm B=46mm C=27mm
D=135mm E=27mm F=54mm





Features

PRODUCT NAME	VIALED-NET
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES

VIALED-NET
LVE1801-G

SYSTEM POWER (W) :	4,5W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	360lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	360lm
POWER SUPPLY (V) :	220-230V
LIGHT SOURCE	LED
WITH LIGHT SOURCE	NON
PROTECTION CLASS	IP20
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	GRIS RAL 7035
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	27mm
LENGTH (MM) :	182mm
WIDTH (MM) :	42mm
MOUNTING WIDTH	182mm
PRODUCT WEIGHT (G) :	650GR
NUMBER OF PRODUCTS PER BOX	8
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	-
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	0
EAN	8021046123173
COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-2-22 EN 61347-1 EN 61347-2-13 EN 61347-2-7 EN 62384 RoHS2 2011/65/UE
INSTALLATION METHOD	Built-in
NOMINAL OPERATING TIME	1h
PROTECTION CLASS	II

Accessories

L99150 - COMMANDER

