VIALED-NET
LVN1501


IP20 IK07 1 pcs

VIALED NET 320lm 2h SPY SYSTEM

The Vialed Net remote power system allows you to connect up to four Vialed luminaires in a fully flexible configuration—star, cascade, or mixed. This system is ideal for spaces that are difficult to access or very confined.



CODE	LVN1501
POWER (W)	
AUTONOMY (U)	2h
TYPE	
RESCUE (LM)	320lm
PERMANENT (LM)	320lm
BATTERY	LI-FEPO4



A=182mm B=46mm C=27mm
D=135mm E=27mm F=54mm

Features

PRODUCT NAME	VIALED-NET
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES

VIALED-NET
LVN1501

LIGHT OUTPUT IN EMERGENCY MODE (LM) :	320lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	320lm
SURVEILLANCE SYSTEM INSTALLATION	SURVEILLANCE CENTRALISEE
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP20
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	WHITE RAL 9003
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	27mm
LENGTH (MM) :	182mm
WIDTH (MM) :	42mm
MOUNTING WIDTH	182mm
PRODUCT WEIGHT (G) :	650GR
NUMBER OF PRODUCTS PER BOX	1
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B208035020
RECUPEL CODE	-
BATTERY WEIGHT (G) :	81 gr.
EAN	8021046121605

COMPLIANT WITH EUROPEAN STANDARDS	EN 60598-2-22 EN 61347-1 EN 61347-2-13 EN 61347-2-7 EN 62384 RoHS2 2011/65/UE
INSTALLATION METHOD	Built-in
MODE	Bus/spy system Security
NOMINAL OPERATING TIME	2h
PROTECTION CLASS	II

Accessories

L99150 - COMMANDER

