# VIALED-NET
# LVE1801-B-SIGN-12


IP20 IK07 1 pcs

**VIALED NET SIGN RIGHT & LEFT 4,5W 360lm WHITE**


The Vialed Net remote power system allows you to connect up to four Vialed luminaires in a fully flexible configuration—star, cascade, or mixed. This system is ideal for spaces that are difficult to access or very confined.



| | |
|---|---|
| **CODE** | LVE1801-B-SIGN-12 |
| **POWER (W)** | 4,5W |
| **AUTONOMY (U)** | 2h |
| **TYPE** | |
| **RESCUE (LM)** | 360lm |
| **PERMANENT (LM)** | 360lm |
| **BATTERY** | |




A=182mm B=46mm C=27mm
D=135mm E=27mm F=54mm




## Features

| | |
|---|---|
| PRODUCT NAME | VIALED-NET |
| PRODUCT FUNCTION | LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES |
| SYSTEM POWER (W) : | 4,5W |
| LIGHT OUTPUT IN EMERGENCY MODE (LM) : | 360lm |
| CONTINUOUS MODE LUMINOUS FLOW (LM) : | 360lm |

# VIALED-NET
# LVE1801-B-SIGN-12

| | |
|---|---|
| POWER SUPPLY (V) : | 220-230V |
| LIGHT SOURCE | LED |
| WITH LIGHT SOURCE | NON |
| PROTECTION CLASS | IP20 |
| HOUSING MATERIAL | POLYCARBONATE |
| HOUSING COLOUR | WHITE RAL 9003 |
| MATERIAL OF THE COVER | TRANSPARENTE PLASTIC |
| IMPACT RESISTANCE | IK07 |
| HEIGHT/DEPTH (MM) : | 27mm |
| LENGTH (MM) : | 182mm |
| WIDTH (MM) : | 42mm |
| FLUSH-MOUNTED DIAMETER (MM) : | 65mm |
| MOUNTING WIDTH | 182mm |
| PRODUCT WEIGHT (G) : | 650GR |
| NUMBER OF PRODUCTS PER BOX | 1 |
| INCANDESCENT WIRE 850°C | OUI |
| CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC | YES |
| VOLTAGE TYPE | AC |
| NONIMAL LIFETIME L70/B50 (H) : | 50.000H (L70B50) |
| RATED AMBIENT TEMPERATURE TO IEC 62722-2-1 | 0°C / +40 °C |
| GUARANTEE | 5 YEARS |
| TYPE OF PACKAGING | CARTON BOX |
| NUMBER OF UNITS IN PACKAGING | 1 |
| INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES | YES |
| BEBAT CODE | - |
| RECUPEL CODE | 5.56 |
| BATTERY WEIGHT (G) : | 0 |
| EAN | 9900000007706 |
| COMPLIANT WITH EUROPEAN STANDARDS | EN 60598-1<br>EN 60598-2-22 |
| FUNCTION | Evacuation lighting |
| INSTALLATION METHOD | Built-in |
| LIGHT DISTRIBUTION ELEMENT | Diffuser |
| NOMINAL OPERATING TIME | 2h |
| PICTOGRAM VISIBILITY | Double-sided<br>Only on one side |
| PROTECTION CLASS | II |
| TYPE OF PICTOGRAM | Acrylic glass plate |

## Accessories

**L99150** - COMMANDER

