# VIALED-NET
# LVH1801-N


8 pcs

**VIALED NET HIGH 4,5W 355lm BLACK**


The Vialed Net remote power system allows you to connect up to four Vialed luminaires in a fully flexible configuration—star, cascade, or mixed. This system is ideal for spaces that are difficult to access or very confined.




| | |
|---|---|
| **CODE** | LVH1801-N |
| **POWER (W)** | 4,5W |
| **AUTONOMY (U)** | 1h |
| **TYPE** | |
| **RESCUE (LM)** | 355lm |
| **PERMANENT (LM)** | 355lm |
| **BATTERY** | |




A=182mm B=46mm C=27mm
D=135mm E=27mm F=54mm




## Features

| | |
|---|---|
| PRODUCT NAME | VIALED-NET |
| PRODUCT FUNCTION | LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES |

| | |
|---|---|
| SYSTEM POWER (W) : | 4,5W |
| LIGHT OUTPUT IN EMERGENCY MODE (LM) : | 355lm |
| CONTINUOUS MODE LUMINOUS FLOW (LM) : | 355lm |
| WITH LIGHT SOURCE | NON |
| HOUSING MATERIAL | POLYCARBONATE |
| HOUSING COLOUR | NOIR RAL 9005 |
| HEIGHT/DEPTH (MM) : | 27mm |
| LENGTH (MM) : | 182mm |
| WIDTH (MM) : | 42mm |
| MOUNTING WIDTH | 182mm |
| PRODUCT WEIGHT (G) : | 650GR |
| NUMBER OF PRODUCTS PER BOX | 8 |
| INCANDESCENT WIRE 850°C | OUI |
| VOLTAGE TYPE | AC |
| RATED AMBIENT TEMPERATURE TO IEC 62722-2-1 | 0°C / +40 °C |
| INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES | YES |
| BEBAT CODE | - |
| RECUPEL CODE | 5.56 |
| BATTERY WEIGHT (G) : | 0 |
| EAN PACK | 8021046345575 |
| COMPLIANT WITH EUROPEAN STANDARDS | EN 60598-1<br>EN 60598-2-22 |
| INSTALLATION METHOD | Built-in |
| NOMINAL OPERATING TIME | 1h |
| PROTECTION CLASS | II |

## Accessories

**L99150** - COMMANDER

