VIALED-NET
LVN1301-IP65


IP65 IK07 1 pcs

VIALED NET 320lm 2h IP65 AUT

The Vialed Net remote power system allows you to connect up to four Vialed luminaires in a fully flexible configuration—star, cascade, or mixed. This system is ideal for spaces that are difficult to access or very confined.



CODE	LVN1301-IP65
POWER (W)	
AUTONOMY (U)	2h
TYPE	
RESCUE (LM)	320lm
PERMANENT (LM)	320lm
BATTERY	LI-FEPO4



A=182mm B=46mm C=27mm
D=135mm E=27mm F=54mm

Features

PRODUCT NAME	VIALED-NET
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES

VIALED-NET
LVN1301-IP65

LIGHT OUTPUT IN EMERGENCY MODE (LM) :	320lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	320lm
WITH CONNECTION TO A IMPULSE RELAY	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP65
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	WHITE RAL 9003
MATERIAL OF THE COVER	TRANSPARENTE PLASTIC
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	27mm
LENGTH (MM) :	182mm
WIDTH (MM) :	42mm
MOUNTING WIDTH	182mm
PRODUCT WEIGHT (G) :	650GR
NUMBER OF PRODUCTS PER BOX	1
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020590
RECUPEL CODE	-
BATTERY WEIGHT (G) :	81 gr.
EAN	8021046115888

COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-2-22 EN 61347-1 EN 61347-2-13 EN 61347-2-7 EN 62034 EN 62384 RoHS2 2011/65/UE
INSTALLATION METHOD	Built-in
MODE	Autotest Security
NOMINAL OPERATING TIME	2h
PROTECTION CLASS	II

Accessories

L99150 - COMMANDER

