VIALED-ROUND
L8123-B-ROUND


IP42 IK08 12 pcs


VIALED ROUND 3,5W 310lm 1h 150lm 3h P/NP WHITE AUT


The Vialed ROUND is the minimalist surface-mounted version of the Vialed Evo. It comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation.



CODE	L8123-B-ROUND
POWER (W)	3,5W
AUTONOMY (U)	1h
	3h
TYPE	Not permanent-
	Permanent
RESCUE (LM)	310lm (1h) 150lm (3h)
PERMANENT (LM)	310lm - 150lm
BATTERY	LI-FEPO4







Features

PRODUCT NAME	VIALED-ROUND
PRODUCT FUNCTION	LUMINAIRES DE SECOURS LED NON-HERMÉTIQUES
SYSTEM POWER (W) :	3,5W

VIALED-ROUND
L8123-B-ROUND

LIGHT OUTPUT IN EMERGENCY MODE (LM) :	310lm (1h) 150lm (3h)
CONTINUOUS MODE LUMINOUS FLOW (LM) :	310lm - 150lm
WITH CONNECTION TO A IMPULSE RELAY	YES
WITH REMOTE CONTROL (COMMANDER)	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4 6.4V 600mAh
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP42
HOUSING MATERIAL	POLYCARBONATE
HOUSING COLOUR	WHITE RAL 9003
MATERIAL OF THE COVER	LENTILLE TRANSPARENTE
IMPACT RESISTANCE	IK08
HEIGHT/DEPTH (MM) :	47mm
EXTERNAL DIAMETER (MM) :	100mm
PRODUCT WEIGHT (G) :	900GR
NUMBER OF PRODUCTS PER BOX	12
INCANDESCENT WIRE 850°C	OUI
CONFORMS TO DIRECTIONS: 89/336/EEC, 73/23/EEC, 98/68/EEC	YES
BATTERY STATUS	LI-FEPO4
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	-5°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020446
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	41
EAN	9900000008093
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 EN 62034 RoHS2 2011/65/UE
FUNCTION	Ambient and evacuation lighting Ambient lighting (anti-panic)

VIALED-ROUND
L8123-B-ROUND

INSTALLATION METHOD	Surface mounting (ceiling)
LIGHT DISTRIBUTION ELEMENT	Focal lens Refraction lens
MODE	Autotest Security
NOMINAL OPERATING TIME	1h 3h
PROTECTION CLASS	II
TYPE OF SWITCHING	Not permanent Permanent

Accessories

L9999-B-1-2 - VIALED ROUND PLEXI 205x105 LEFT & RIGHT WHITE



L9999-B-3 - VIALED ROUND PLEXI 205x105 DOWN WHITE



L9999-B-4 - VIALED ROUND PLEXI 205x105 EXIT WHITE



L9999-B-5 - VIALED ROUND PLEXI 205x105 EXTINGUISHER WHITE



L9999-B-6 - VIALED ROUND PLEXI 205x105 HYDRANT WHITE



L9920-B - VIALED ROUND RECESSED KIT

