VIALED-SIGN
L8106-B-DALI-SIGN-3


IP20 IP42 IK07 8 pcs

VIALED SIGN DOWN 0,4W 3h DALI 360lm NM WHITE

The Vialed Sign is a minimalist signaling luminaire with a very discreet design. It comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation. The metal ring is available in white, gray, or black.



CODE	L8106-B-DALI-SIGN-3
POWER (W)	0,4W
AUTONOMY (U)	3h
TYPE	Not permanent
RESCUE (LM)	360lm
PERMANENT (LM)	
BATTERY	LI-FEPO4



Features

PRODUCT NAME	VIALED-SIGN
PRODUCT FUNCTION	EMERGENCY AND SIGNAL LIGHTING

VIALED-SIGN
L8106-B-DALI-SIGN-3

SYSTEM POWER (W) :	0,4W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	360lm
SURVEILLANCE SYSTEM INSTALLATION	DALI
WITH CONNECTION TO A IMPULSE RELAY	YES
WITH REMOTE CONTROL (COMMANDER)	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP20/IP42
HOUSING MATERIAL	FONTE D'ALUMINIUM
HOUSING COLOUR	WHITE RAL 9003
MATERIAL OF THE COVER	LENTILLE TRANSPARENTE
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	3,2mm
EXTERNAL DIAMETER (MM) :	85mm
FLUSH-MOUNTED DIAMETER (MM) :	65mm
MOUNTING WIDTH	85mm
PRODUCT WEIGHT (G) :	800GR
NUMBER OF PRODUCTS PER BOX	8
INCANDESCENT WIRE 850°C	OUI
BATTERY STATUS	LI-FEPO4
INCLUDED PICTOGRAMS	OUI
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
ENEC	YES
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020590
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	81 gr.
EAN	9900000006259
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 ISO 7010

VIALED-SIGN
L8106-B-DALI-SIGN-3

FUNCTION	Ambient and evacuation lighting
INSTALLATION METHOD	Built-in
LIGHT DISTRIBUTION ELEMENT	Focal lens Refraction lens
MODE	Dali Security
NOMINAL OPERATING TIME	3h
PICTOGRAM VISIBILITY	Only on one side
PROTECTION CLASS	II
TYPE OF SWITCHING	Not permanent

Accessories

L99150 - COMMANDER



L99157 - INHIBITION KIT FOR PERMANENT VERSION

