VIALED-SIGN
L8121-N-SIGN-3


IP20 IP42 IK07 8 pcs

VIALED SIGN DOWN 5,7W 1h 450lm M/NM BLACK

The Vialed Sign is a minimalist signaling luminaire with a very discreet design. It comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation. The metal ring is available in white, gray, or black.



CODE	L8121-N-SIGN-3
POWER (W)	5,7W
AUTONOMY (U)	1h
TYPE	Not permanent-Permanent
RESCUE (LM)	450lm
PERMANENT (LM)	450lm
BATTERY	LI-FEPO4





Features

PRODUCT NAME	VIALED-SIGN
PRODUCT FUNCTION	EMERGENCY AND SIGNAL LIGHTING
SYSTEM POWER (W) :	5,7W
LIGHT OUTPUT IN EMERGENCY MODE (LM) :	450lm
CONTINUOUS MODE LUMINOUS FLOW (LM) :	450lm
SURVEILLANCE SYSTEM INSTALLATION	SANS

VIALED-SIGN
L8121-N-SIGN-3

WITH CONNECTION TO A IMPULSE RELAY	YES
WITH REMOTE CONTROL (COMMANDER)	YES
POWER SUPPLY (V) :	220-230V
BATTERY	LiFePO4
BATTERY RECHARGE TIME (H) :	12H
LIGHT SOURCE	LED
WITH LIGHT SOURCE	YES
PROTECTION CLASS	IP20/IP42
HOUSING MATERIAL	FONTE D'ALUMINIUM
HOUSING COLOUR	NOIR RAL 9005
MATERIAL OF THE COVER	LENTILLE TRANSPARENTE
IMPACT RESISTANCE	IK07
HEIGHT/DEPTH (MM) :	3,2mm
EXTERNAL DIAMETER (MM) :	85mm
FLUSH-MOUNTED DIAMETER (MM) :	65mm
MOUNTING WIDTH	85mm
PRODUCT WEIGHT (G) :	800GR
NUMBER OF PRODUCTS PER BOX	8
INCANDESCENT WIRE 850°C	OUI
BATTERY STATUS	LI-FEPO4
INCLUDED PICTOGRAMS	OUI
VOLTAGE TYPE	AC
NONIMAL LIFETIME L70/B50 (H) :	50.000H (L70B50)
RATED AMBIENT TEMPERATURE TO IEC 62722-2-1	0°C / +40 °C
GUARANTEE	5 YEARS
TYPE OF PACKAGING	CARTON BOX
NUMBER OF UNITS IN PACKAGING	1
ENEC	YES
INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES	YES
BEBAT CODE	B110020446
RECUPEL CODE	5.56
BATTERY WEIGHT (G) :	41
EAN	9900000006365
COMPLIANT WITH EUROPEAN STANDARDS	EN 1838 EN 60598-1 EN 60598-2-22 ISO 7010
FUNCTION	Ambient and evacuation lighting
INSTALLATION METHOD	Built-in

LIGHT DISTRIBUTION ELEMENT	Focal lens Refraction lens
MODE	Security Standard
NOMINAL OPERATING TIME	1h
PICTOGRAM VISIBILITY	Only on one side
PROTECTION CLASS	II
TYPE OF SWITCHING	Not permanent Permanent

Accessories

L99150 - COMMANDER



L99157 - INHIBITION KIT FOR PERMANENT VERSION

