# VIALED-SIGN
## L8126-N-DALI-SIGN-4


IP20 IP42 IK07 8 pcs


**VIALED SIGN EXIT 5,7W 3h DALI 360lm N/NM BLACK**


The Vialed Sign is a minimalist signaling luminaire with a very discreet design. It comes standard with two lenses, one symmetrical and one asymmetrical, providing more flexibility during installation. The metal ring is available in white, gray, or black.



| | |
|---|---|
| **CODE** | L8126-N-DALI-SIGN-4 |
| **POWER (W)** | 5,7W |
| **AUTONOMY (U)** | 3h |
| **TYPE** | Permanent |
| **RESCUE (LM)** | 360lm |
| **PERMANENT (LM)** | 360lm |
| **BATTERY** | LI-FEPO4 |




## Features

| | |
|---|---|
| PRODUCT NAME | VIALED-SIGN |
| PRODUCT FUNCTION | EMERGENCY AND SIGNAL LIGHTING |

# VIALED-SIGN
## L8126-N-DALI-SIGN-4

| | |
|---|---|
| SYSTEM POWER (W) : | 5,7W |
| LIGHT OUTPUT IN EMERGENCY MODE (LM) : | 360lm |
| CONTINUOUS MODE LUMINOUS FLOW (LM) : | 360lm |
| SURVEILLANCE SYSTEM INSTALLATION | DALI |
| WITH CONNECTION TO A IMPULSE RELAY | YES |
| WITH REMOTE CONTROL (COMMANDER) | YES |
| POWER SUPPLY (V) : | 220-230V |
| BATTERY | LiFePO4 |
| BATTERY RECHARGE TIME (H) : | 12H |
| LIGHT SOURCE | LED |
| WITH LIGHT SOURCE | YES |
| PROTECTION CLASS | IP20/IP42 |
| HOUSING MATERIAL | FONTE D'ALUMINIUM |
| HOUSING COLOUR | NOIR RAL 9005 |
| MATERIAL OF THE COVER | LENTILLE TRANSPARENTE |
| IMPACT RESISTANCE | IK07 |
| HEIGHT/DEPTH (MM) : | 3,2mm |
| EXTERNAL DIAMETER (MM) : | 85mm |
| FLUSH-MOUNTED DIAMETER (MM) : | 65mm |
| MOUNTING WIDTH | 85mm |
| PRODUCT WEIGHT (G) : | 800GR |
| NUMBER OF PRODUCTS PER BOX | 8 |
| INCANDESCENT WIRE 850°C | OUI |
| BATTERY STATUS | LI-FEPO4 |
| INCLUDED PICTOGRAMS | OUI |
| VOLTAGE TYPE | AC |
| NONIMAL LIFETIME L70/B50 (H) : | 50.000H (L70B50) |
| RATED AMBIENT TEMPERATURE TO IEC 62722-2-1 | 0°C / +40 °C |
| GUARANTEE | 5 YEARS |
| TYPE OF PACKAGING | CARTON BOX |
| NUMBER OF UNITS IN PACKAGING | 1 |
| ENEC | YES |
| INSTALLATION SUR SURFACES NORMALEMENT INFLAMMABLES | YES |
| BEBAT CODE | B110020590 |
| RECUPEL CODE | 5.56 |
| BATTERY WEIGHT (G) : | 81 gr. |
| EAN | 9900000007621 |

# VIALED-SIGN
# L8126-N-DALI-SIGN-4

| | |
|---|---|
| COMPLIANT WITH EUROPEAN STANDARDS | EN 1838<br>EN 60598-1<br>EN 60598-2-22<br>ISO 7010 |
| FUNCTION | Ambient and evacuation lighting |
| INSTALLATION METHOD | Built-in |
| LIGHT DISTRIBUTION ELEMENT | Focal lens<br>Refraction lens |
| MODE | Dali<br>Security |
| NOMINAL OPERATING TIME | 3h |
| PICTOGRAM VISIBILITY | Only on one side |
| PROTECTION CLASS | II |
| TYPE OF SWITCHING | Permanent |

## Accessories

**L99150** - COMMANDER



**L99157** - INHIBITION KIT FOR PERMANENT VERSION

